

LTP

Transformer & Power

A. d. Schleifmuehle 37
28203 Bremen, Germany

TECHNICAL SPECIFICATION

NAME: Three -phase oil-Immersed transformer according to IEC 60076- BS 171, with conservator, , suitable for outdoor installation, a maximum ambient temperature of 45 ° C and maximum altitude for installation of 1000 m above sea level, with copper windings, routine test and Tolerance according to IEC60076- BS 171

Model-LTP

Type -Model	: LTP- 1000/11	Cooling method	: ONAN
Rated Capacity KVA	: 1000 K.V.A.	Operating duty	: DB
Rated Voltage	: 11000/415 Volts	Frequency (Hz)	: 50
Rated current	: 52.48 / 1387.9 Amps.	Mode	: HT
Tapping	: HV side in 4 steps of 2.5%	Class of Insulation Material	: A
	: +5% to – 5%	Mounting	: Ground
Vector Group	: Dyn 11		
Neutral Point	: taken out on LV side with		100% rating inside L.V. Cable Box.

No load losses W	: 1500 Tolerance : + 15%	DIMENSIONS (Approximate)	
Load losses at 75°C W	: 12000 Tolerance : + 15%	Length (mm)	: 1950
Total losses W	: 13500 Tolerance : + 10%	Width (mm)	: 1900
Short circuit voltage At 75°C (Impedance)	: 5.50 %	Height (mm)	: 1950
Oil Quantity (Approx.)	: 715 Kgs./ 850 Litres		
Total Weight (Kg)	: 3300		

Regulation at Rated Current	At U.P.F. 1.21%	At 0.80 P.F. 3.66%	
Efficiency at Rated Current	: At 125% 98.72%	: At 100% 98.75%	
	: At 75% 99.00%	: At 50% 99.19%	
	: At 25% 99.17%	: ---	

Standard Accessories : As per customer's specifications

Bushings : HV 3 pcs. IS:3347 similar to DIN 42531 **(Cable Box)**
: LV 4 pcs. IS:3347 similar to DIN 42530 **(Cable Box)**

Painting : Standard Transformer Colour or as per customer's requirement

Notes : Max. ambient temperature 45°C
: Max. over temperature of oil 50°C
: Max. over temperature of winding 55°C
: Lightning Impulse withstand test 70 K.V.R.M.S.
: Applied Voltage withstand test HV 28 K.V.R.M.S.
LV 3 K.V.R.M.S.

Inscription : English

LTP Transformer & Power

Bremen