



# TRANS TECH HANDELS GMBH

A.d. Schleifmuehle 37  
28203 Bremen, Germany

## TECHNICAL SPECIFICATION

**NAME:** Three - phase oil - immersed transformer according to IEC60076 – BS 171, with conservator, suitable for outdoor installation, a maximum ambient temperature of 45°C and maximum altitude for installation of 1000 m above sea level, with copper windings, routine test and Tolerance according to IEC 60076-BS 171

|                           |                                                             |                                     |        |
|---------------------------|-------------------------------------------------------------|-------------------------------------|--------|
| <b>Type</b>               | : TTH 300/33                                                | <b>Cooling method</b>               | : ONAN |
| <b>Rated Capacity KVA</b> | : 300 KVA                                                   | <b>Operating duty</b>               | : DB   |
| <b>Rated Voltage</b>      | : 33000/415 Volts                                           | <b>Frequency (Hz)</b>               | : 50   |
| <b>Rated current</b>      | : 5.25/417.36 Amps.                                         | <b>Mode</b>                         | : LT   |
| <b>Tapping</b>            | : HV side in 6 steps of 2.5%<br>: +5% to -7.5%              | <b>Class of Insulation Material</b> | : A    |
| <b>Vector Group</b>       | : Dyn 11                                                    |                                     |        |
| <b>Neutral Point</b>      | : taken out on LV side with 100% rating inside LV Cable Box |                                     |        |

|                                                  |                      |                   |
|--------------------------------------------------|----------------------|-------------------|
| <b>No load losses W</b>                          | : 670                | Tolerance : + 15% |
| <b>Load losses at 75°C W</b>                     | : 4300               | Tolerance : + 15% |
| <b>Total losses W</b>                            | : 4970               | Tolerance : + 10% |
| <b>Short circuit voltage At 75°C (Impedance)</b> | : 4.75 %             |                   |
| <b>Oil Quantity (Approx.)</b>                    | : 400 Kg./ 482 Litre |                   |
| <b>Total Weight (Kg)</b>                         | : 1505               |                   |

### DIMENSIONS (Approximate)

|                    |        |
|--------------------|--------|
| <b>Length (mm)</b> | : 1225 |
| <b>Width (mm)</b>  | : 1050 |
| <b>Height (mm)</b> | : 2030 |

|                                    |                 |                    |
|------------------------------------|-----------------|--------------------|
| <b>Regulation at Rated Current</b> | At U.P.F. 1.54% | At 0.80 P.F. 3.90% |
| <b>Efficiency at Rated Current</b> | At 125% 98.07%  | At 100% 98.37%     |
|                                    | At 75% 98.65%   | At 50% 98.85%      |
|                                    | At 25% 98.76%   | ---                |

**Standard Accessories** : As per GA Drawing 3-300/A-3/1

**Bushings** : HV 3 pcs. IS:3347 similar to DIN 42531  
: LV 4 pcs. IS:3347 similar to DIN 42530 (**Cable Box**)

**Painting** : Standard Transformer Colour or as per customer's requirement

**Notes** : Max. ambient temperature 45°C  
: Max. over temperature of oil 55°C  
: Max. over temperature of winding 65°C  
: Lightning Impulse withstand test 200 KVP  
: Applied Voltage withstand test HV 70 KVRMS  
LV 3 KVRMS

**Inscription** : English

Trans Tech Handels GmbH

Bremen